

INFINITY PRINT SOLUTIONS



Infinity Pay As You Go

How it Works

Infinity Print Solutions will supply and install the printer with 3 toner cartridges (one in the machine and 2 spare). In the costs of consumables, we include all labour costs of our service and maintenance call out capability (which is considerably more responsive than the Manufacturer's warranty service).

There are no long term contracts all we ask is you provide 30 days written notice if you wish to cancel this printer or your needs change and you require different options or facilities.

Kyocera P2235dn

Cartridges

Cartridge	Yield @5%	Cost
TK-1150	3000	£40.00

Features

Size	A4 35ppm
Mode	MONO
Networking	YES
Duplex	YES
Scan and Copy	NO
Fax	NO

Initial Cost

3 X Cartridges	£120.00
Setup and Installation**	£75.00
Total Cost	£195.00

Key Benefits

- Free printer for the duration you require it
- Maintenance inclusive of parts, labour and call out
- No long term commitment
- No Volume of cartridge purchase commitment.
- Upgrade or cancel with 30 days written notice
- Reduce your printer costs
- Reduce your carbon footprint

**All prices shown are exclusive of V.A.T

*set up and installation includes: administration costs plus plug in, connect to 2 PC's on the same operating system via USB or network or on a network server once to an existing printer location – additional work via quote, cables not included.



> PRINT

ECOSYS P2235dn
ECOSYS P2235dw

B/W DESKTOP PRINTER
FOR A4 FORMAT

TOUGH DESKTOP PRINTERS THAT GO THE EXTRA MILE.



A lot of printing power is hidden under the modern housing of the new P2235 devices: a print speed of up to 35 pages per minute, standard duplex functionality for double-sided printing and a paper capacity of up to 850 sheets. As to expect from KYOCERA, they are extremely reliable devices with long-life components and a low TCO. But there's more: The print resolution is a remarkable 1,200 dpi, resulting in very sharp and detailed printouts you may not expect from printers in this range. And with the P2235dw, you also have standard Wi-Fi, including Wi-Fi direct functionality, giving you even more flexibility.

- > Up to 35 pages per minute in A4
- > Standard duplex functionality for double-sided printing
- > High printing resolution of up to 1,200 dpi
- > USB and network connectivity as standard
- > Compact design, robust and quiet
- > Highly reliable thanks to long-life components
- > Exceptionally low printing costs



ECOSYS stands for ECOlogy, ECONomy and SYStem-printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that toner is the only consumable. The modular design concept allows you to add workflow enhancing functions as required. Integrated system software provides long-term cross network compatibility. KYOCERA's long-life components cost you and the environment less.

Environmental print features

Duplex print mode (Double sided printing), N-Up printing mode (N pages on 1 sheet), Toner save mode (Draft print mode), Quiet mode (reduced print speed).

KYOCERA NetViewer

KYOCERA NetViewer enables complete monitoring and control of all ECOSYS printers and digital KYOCERA multifunction units from any Windows® PC and thus provides ideal network administration. It also supports the standardised SNMP protocol.

ECOSYS P2235dn/ECOSYS P2235dw

GENERAL

Technology: KYOCERA ECOSYS Laser

Engine speed: Up to 35 pages A4 per minute

Print resolution: 300 dpi, 600 dpi, 1200 dpi

Duty cycle: Max. 20,000 pages per month

Warm-up time: Approx. 15 seconds or less

Time to first print: Approx. 6.8 seconds or less

CPU: 800 MHz

Memory: Standard 256 MB, max. 256 MB

Standard interface:

ECOSYS P2235dn: USB 2.0 (Hi-Speed), USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT), Slot for optional SD/SDHC-Card

ECOSYS P2235dw: USB 2.0 (Hi-Speed), USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT), Wireless LAN, Slot for optional SD/SDHC-Card

Dimensions (W x D x H): Main unit: 375 x 393 x 272 mm

Weight: Main unit: Approx. 14 kg

Power source: AC 220 ~ 240 V, 50/60 Hz

Power consumption:

Printing: 620 W

Ready mode: 8 W

Sleep mode: 0.8 W

Noise (Sound pressure level: ISO 7779/ISO 9296):

Printing: 47.9 dB(A) LpA

Ready/Standby mode: Immeasurably low

Sleep mode: Immeasurably low

Safety standards: GS, TÜV, CE

This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

Command Center RX

The Command Center RX enables to control and manage various settings by accessing the device via Web browser.

USB Host Interface for USB Flash Memory

Documents can be printed directly from a USB Flash Memory (e.g. USB stick) via the USB host interface. The documents stored as PDF, XPS, TIFF or JPEG are selected directly via the printer's control panel. No computer is required.

Application-based Profiles

The KX printer driver can create a direct link between dedicated applications and predefined or customised print profiles. You can set that all documents from a user or an application be printed with activated duplex mode as standard, thus leading to a reduced paper consumption.

PAPER HANDLING

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity: 100-sheet multi-purpose tray; 60 – 220 g/m²; A4, A5, A6, B5, B6, Letter, Legal, Custom (70 x 148 mm – 216 x 356 mm) 250-sheet universal cassette; 60 – 163 g/m²; A4, A5, A6, B5, Letter, Legal, Custom (105 x 148 – 216 x 356 mm). Max. input capacity with options: 850 sheets

Duplex functionality as standard: Double-sided printing; 60 – 163 g/m²; A4, A5, B5, Letter, Legal

Output capacity: Max. 250 sheet face down

PRINT FUNCTIONS

Controller language: PRESCRIBE IIc

Emulations: PCL 6 (PCL 5e/PCL-XL), PostScript 3 (KPDL 3), XPS/OpenXPS

Operating systems: All current Windows operating systems, MAC OS X Version 10.5 or higher, Unix, Linux as well as other operating systems on request

Fonts/barcodes: 93 scalable fonts for PCL6/KPDL3, 8 fonts for Windows Vista, 1 bitmap font, 45 barcodes (e.g. EAN8, EAN13) with automatic generation of check-sums as well as support of two-dimensional barcodes PDF-417 under PRESCRIBE (PCL and other barcodes available as an option)

CONSUMABLES

Average continuous toner yield in accordance with ISO/IEC 19752

Toner-Kit TK-1150: toner yield 3,000 pages A4
Starter toner: toner yield 1,000 pages A4

OPTIONS

PF-1100 Paper feeder (max. 2 units): 250 sheets; 60 – 163 g/m²; A4, A5, A6, B5, Letter, Legal, Custom (105 x 148 mm – 216 x 356 mm)

UG-33: ThinPrint support

USB IC Card Reader + Card Authentication Kit (B): Support for various authentication keys available

CB-1100: Wooden cabinet

MODEL VARIATIONS

ECOSYS P2235DN/KL3: ECOSYS P2235DN incl. warranty extension KYOLife 3 years

ECOSYS P2235DW/KL3: ECOSYS P2235DW incl. warranty extension KYOLife 3 years


WARRANTY

1-year warranty** as standard. KYOCERA guarantees the drum and developer for 3 years or maximum 100,000 pages A4 (whichever occurs sooner), provided the printer is used and cleaned in accordance with the service instructions.

KYOLIFE The up to 5-year on-site warranty extension for printer and options.



OCT2016/ECOSYSP2235DN/P2235DW



KYOCERA Document Solutions Europe B.V. – Branch Office Germany
Otto-Hahn-Straße 12 – 40670 Meerbusch – Germany
Tel +49 (0) 2159 928-500 – Fax +49 (0) 2159 918-100
www.kyoceradocumentsolutions.eu – info@deu.kyocera.com

KYOCERA Document Solutions Inc. – 2-28, 1-Chome – Tamatsukuri
Chuo-Ku – Osaka 540-8585 – Japan – www.kyoceradocumentsolutions.com

* KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

** Depending on the country

YOUR KYOCERA BUSINESS-PARTNER

